TEST REPORT

IEC 60950-1
Information technology equipment – Safety – Part 1: General requirements

Report Number. :	LCS171221033AS
Date of issue :	2018-01-16
Total number of pages :	71
Applicant's name :	Shenzhen KVD Communication Equipment Limited
Address :	Lenovo R&D Center 2F-B, South First Road, High-tech Park, Nanshan District, Shenzhen, Guangdong, China
Test specification:	
Standard :	IEC 60950-1: 2005+A1: 2009+A2: 2013
Test procedure :	Type test
Non-standard test method :	N/A
Test Report Form No. :	IEC60950_1F
Test Report Form(s) Originator :	SGS Fimko Ltd
Master TRF :	Dated 2014-02

Copyright © 2014 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.

General disclaimer:

The test results presented in this report relate only to the object tested.
This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Test item description .....:	LTE GSM/WCDMA Smartphone
Trade Mark .....:	DOOGEE
Manufacturer.....:	Same as applicant
Model/Type reference .....:	S60 Lite
Ratings .....:	Input : 7V⎓, 3A or 9V⎓, 2.7A or 12V⎓, 2A; For battery: 3.8V⎓, 5580mAh

Testing procedure and testing location:			
☒	**Testing Laboratory:**	Shenzhen LCS Compliance Testing Laboratory Ltd.	
Testing location/ address ..... :		1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China	
☐	**Associated Testing Laboratory:**	N/A	
Testing location/ address ..... :		N/A	
Tested by (name + signature) ..... :		Jowie Jiao	Jowie Jiao
Checked by (name + signature) ..... :		Peter Chen	Peter Chen
Approved by (name + signature) ..... :		Hart Qiu	Hart Qiu
☐	**Testing procedure: Elsewhere:**		
Testing location/ address ..... :			
Tested by (name + signature) ..... :			
Approved by (name + signature) ..... :			

List of Attachments (including a total number of pages in each attachment):

Attachment No. 1	Attachment To Test Report IEC 60950-1 European Group Differences And National Differences(18 pages)
Attachment No. 2	EN62471 test data (5 pages.)
Attachment No. 3	50332-1 and 50332-2 test data (2 pages.)
Attachment No. 4	Photo document (8 pages.)

Summary of testing:

Tests performed (name of test and test clause):	**Testing location:**
The submitted samples were found to comply with the requirements of: ➢ Electrical safety IEC 60950-1(ed.2);am1;am2	Shenzhen LCS Compliance Testing Laboratory Ltd. 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

Summary of compliance with National Differences:

List of countries addressed: National Differences and Group Differences, Refer Attachment No. 1 for details

☒ The product fulfils the requirements of EN 60950-1: 2006+A11: 2009+A1: 2010+A12: 2011+A2: 2013.

Copy of marking plate:

The artwork below may be only a draft.

DOOGEE
LTE GSM/WCDMA Smartphone
Model: S60 Lite
Input : 7V⎓, 3A or 9V⎓, 2.7A or 12V⎓, 2A
For battery: 3.8V⎓, 5580mAh
Importer: XXXX
Address: XXXX



Shenzhen KVD Communication Equipment Limited

Made in China

Remark:

The height dimension of CE mark should not less than 5mm, the height dimension of WEEE symbol should not less than 7mm.

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Test item particulars.....:	
Equipment mobility.....:	[X] movable [X] hand-held [] transportable [] stationary [] for building-in [] direct plug-in
Connection to the mains.....:	[] pluggable equipment [] type A [] type B [] permanent connection [] detachable power supply cord [] non-detachable power supply cord [X] not directly connected to the mains
Operating condition.....:	[X] continuous [] rated operating / resting time:
Access location .....:	[X] operator accessible [] restricted access location
Over voltage category (OVC) .....:	[] OVC I [] OVC II [] OVC III [] OVC IV [X] other: not directly connected to the mains
Mains supply tolerance (%) or absolute mains supply values .....:	N/A
Tested for IT power systems .....:	[] Yes [X] No
IT testing, phase-phase voltage (V) .....:	N/A
Class of equipment .....:	[] Class I [] Class II [X] Class III [] Not classified
Considered current rating of protective device as part of the building installation (A) .....:	N/A
Pollution degree (PD) .....:	[] PD 1 [X] PD 2 [] PD 3
IP protection class .....:	IP20
Altitude during operation (m) .....:	≤ 2000
Altitude of test laboratory (m) .....:	< 500
Mass of equipment (kg) .....:	0.71 approx.
Possible test case verdicts:	
- test case does not apply to the test object.....:	N/A
- test object does meet the requirement.....:	P (Pass)
- test object does not meet the requirement.....:	F (Fail)
Testing.....:	
Date of receipt of test item .....:	2017-12-21
Date (s) of performance of tests.....:	From 2017-12-21 to 2018-01-16

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

General remarks:

"(See Enclosure #)" refers to additional information appended to the report.
"(See appended table)" refers to a table appended to the report.

Throughout this report a ☐ comma / ☒ point is used as the decimal separator.

According to the EU directives which have been aligned with EU NLF (new legislative framework), both of manufacturer and importer's name and address shall be affixed on the product or, where that is not possible, on its packaging or in a document accompanying the product before the product is placed on the EU market.

The manufacturer/ Importer has to ensure the appliance placing on the EU market conforms to the applicable EU directives which provide the affixing of the CE marking, such as LVD, EMC, RoHS, ErP, and so on.

When differences exist; they shall be identified in the General product information section.

Name and address of factory (ies) ..... : Same as applicant

General product information:

1. The product was submitted and tested for use at the manufacturer's recommended ambient temperature (Tma) of 40°C.

Abbreviations used in the report:

- normal conditions	**N.C**.	- single fault conditions	**S.F.C**
- functional insulation	**OP**	- basic insulation	**BI**
- double insulation	**DI**	- supplementary insulation	**SI**
- between parts of opposite polarity	**BOP**	- reinforced insulation	**RI**

Indicate used abbreviations (if any)

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1	**GENERAL**		
1.5	**Components**		P
1.5.1	General		P
	Comply with IEC 60950-1 or relevant component standard	(see appended tables 1.5.1)	P
1.5.2	Evaluation and testing of components		P
1.5.3	Thermal controls		N/A
1.5.4	Transformers		N/A
1.5.5	Interconnecting cables		N/A
1.5.6	Capacitors bridging insulation		N/A
1.5.7	Resistors bridging insulation		N/A
1.5.7.1	Resistors bridging functional, basic or supplementary insulation		N/A
1.5.7.2	Resistors bridging double or reinforced insulation between a.c. mains and other circuits		N/A
1.5.7.3	Resistors bridging double or reinforced insulation between a.c. mains and antenna or coaxial cable		N/A
1.5.8	Components in equipment for IT power systems		N/A
1.5.9	Surge suppressors		N/A
1.5.9.1	General		N/A
1.5.9.2	Protection of VDRs		N/A
1.5.9.3	Bridging of functional insulation by a VDR		N/A
1.5.9.4	Bridging of basic insulation by a VDR		N/A
1.5.9.5	Bridging of supplementary, double or reinforced insulation by a VDR		N/A
1.6	**Power interface**		P
1.6.1	AC power distribution systems	Not directly connected to mains	N/A
1.6.2	Input current	(see appended table 1.6.2)	P
1.6.3	Voltage limit of hand-held equipment	<250V	P
1.6.4	Neutral conductor		N/A
1.7	**Marking and instructions**		P
1.7.1	Power rating and identification markings		P
1.7.1.1	Power rating marking		P
	Multiple mains supply connections.....:		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Rated voltage(s) or voltage range(s) (V) .....:	7V, 9V, 12V	P
	Symbol for nature of supply, for d.c. only.....:	⎓	P
	Rated frequency or rated frequency range (Hz) ....:		N/A
	Rated current (mA or A) .....:	3A, 2.7A, 2A	P
1.7.1.2	Identification markings		P
	Manufacturer's name or trade-mark or identification mark .....:	(see copy of marking plate)	P
	Model identification or type reference .....:	(see copy of marking plate)	P
	Symbol for Class II equipment only .....:	Class III	N/A
	Other markings and symbols .....:	(see copy of marking plate)	P
1.7.1.3	Use of graphical symbols		N/A
1.7.2	Safety instructions and marking	Provided	P
1.7.2.1	General		P
1.7.2.2	Disconnect devices		N/A
1.7.2.3	Overcurrent protective device		N/A
1.7.2.4	IT power distribution systems		N/A
1.7.2.5	Operator access with a tool		N/A
1.7.2.6	Ozone		N/A
1.7.3	Short duty cycles	Continuous operation	N/A
1.7.4	Supply voltage adjustment .....:	No supply voltage adjustment	N/A
	Methods and means of adjustment; reference to installation instructions .....:		N/A
1.7.5	Power outlets on the equipment .....:	No standard power outlets.	N/A
1.7.6	Fuse identification (marking, special fusing characteristics, cross-reference) .....:		N/A
1.7.7	Wiring terminals		N/A
1.7.7.1	Protective earthing and bonding terminals ....:		N/A
1.7.7.2	Terminals for a.c. mains supply conductors		N/A
1.7.7.3	Terminals for d.c. mains supply conductors		N/A
1.7.8	Controls and indicators		P
1.7.8.1	Identification, location and marking .....:		P
1.7.8.2	Colours .....:		P
1.7.8.3	Symbols according to IEC 60417.....:		P
1.7.8.4	Markings using figures .....:		N/A
1.7.9	Isolation of multiple power sources .....:		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7.10	Thermostats and other regulating devices .....:	No such regulating devices	N/A
1.7.11	Durability	The label was subjected to the permanence of marking test. The label was rubbed with cloth soaked with water for 15 sec. And then again for 15 sec. With the cloth soaked with petroleum spirit. After this test there was no damage to the label. The marking on the label did not fade. There was no curling and lifting of the label edge.	P
1.7.12	Removable parts		N/A
1.7.13	Replaceable batteries .....:		N/A
	Language(s) .....:		—
1.7.14	Equipment for restricted access locations.....:		N/A

2	**PROTECTION FROM HAZARDS**		
2.1	**Protection from electric shock and energy hazards**		P
2.1.1	Protection in operator access areas	Supplied by SELV	P
2.1.1.1	Access to energized parts		N/A
	Test by inspection .....:		N/A
	Test with test finger (Figure 2A) .....:		N/A
	Test with test pin (Figure 2B) .....:		N/A
	Test with test probe (Figure 2C) .....:		N/A
2.1.1.2	Battery compartments		N/A
2.1.1.3	Access to ELV wiring		N/A
	Working voltage (Vpeak or Vrms); minimum distance through insulation (mm)		—
2.1.1.4	Access to hazardous voltage circuit wiring		N/A
2.1.1.5	Energy hazards .....:		N/A
2.1.1.6	Manual controls		N/A
2.1.1.7	Discharge of capacitors in equipment		N/A
	Measured voltage (V); time-constant (s).....:		—
2.1.1.8	Energy hazards – d.c. mains supply		N/A
	a) Capacitor connected to the d.c. mains supply ..:		N/A
	b) Internal battery connected to the d.c. mains supply :		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.1.1.9	Audio amplifiers .....:		P
2.1.2	Protection in service access areas		N/A
2.1.3	Protection in restricted access locations		N/A
2.2	**SELV circuits**		P
2.2.1	General requirements		P
2.2.2	Voltages under normal conditions (V) .....:	(see appended table 2.2)	P
2.2.3	Voltages under fault conditions (V) .....:	(see appended table 2.2)	P
2.2.4	Connection of SELV circuits to other circuits .....:	Connect to SELV circuits only	P
2.3	**TNV circuits**		N/A
2.3.1	Limits	No TNV circuits	N/A
	Type of TNV circuits.....:		—
2.3.2	Separation from other circuits and from accessible parts		N/A
2.3.2.1	General requirements		N/A
2.3.2.2	Protection by basic insulation		N/A
2.3.2.3	Protection by earthing		N/A
2.3.2.4	Protection by other constructions .....:		N/A
2.3.3	Separation from hazardous voltages		N/A
	Insulation employed .....:		—
2.3.4	Connection of TNV circuits to other circuits		N/A
	Insulation employed .....:		—
2.3.5	Test for operating voltages generated externally		N/A
2.4	**Limited current circuits**		N/A
2.4.1	General requirements		N/A
2.4.2	Limit values		N/A
	Frequency (Hz) .....:		—
	Measured current (mA) .....:		—
	Measured voltage (V).....:		—
	Measured circuit capacitance (nF or µF) .....:		—
2.4.3	Connection of limited current circuits to other circuits		N/A
2.5	**Limited power sources**		P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	a) Inherently limited output		N/A
	b) Impedance limited output		N/A
	c) Regulating network or IC current limiter, limits output under normal operating and single fault condition	See the table 2.5	P
	Use of integrated circuit (IC) current limiters		N/A
	d) Overcurrent protective device limited output		N/A
	Max. output voltage (V), max. output current (A), max. apparent power (VA) .....:		—
	Current rating of overcurrent protective device (A) .:		—

2.6	**Provisions for earthing and bonding**		N/A
2.6.1	Protective earthing		N/A
2.6.2	Functional earthing		N/A
	Use of symbol for functional earthing .....:		N/A
2.6.3	Protective earthing and protective bonding conductors		N/A
2.6.3.1	General		N/A
2.6.3.2	Size of protective earthing conductors		N/A
	Rated current (A), cross-sectional area (mm^2), AWG.....:		—
2.6.3.3	Size of protective bonding conductors		N/A
	Rated current (A), cross-sectional area (mm^2), AWG.....:		—
	Protective current rating (A), cross-sectional area (mm^2), AWG.....:		—
2.6.3.4	Resistance of earthing conductors and their terminations; resistance (Ω), voltage drop (V), test current (A), duration (min).....:		N/A
2.6.3.5	Colour of insulation .....:		N/A
2.6.4	Terminals		N/A
2.6.4.1	General		N/A
2.6.4.2	Protective earthing and bonding terminals		N/A
	Rated current (A), type, nominal thread diameter (mm).....:		—
2.6.4.3	Separation of the protective earthing conductor from protective bonding conductors		N/A
2.6.5	Integrity of protective earthing		N/A
2.6.5.1	Interconnection of equipment		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.6.5.2	Components in protective earthing conductors and protective bonding conductors		N/A
2.6.5.3	Disconnection of protective earth		N/A
2.6.5.4	Parts that can be removed by an operator		N/A
2.6.5.5	Parts removed during servicing		N/A
2.6.5.6	Corrosion resistance		N/A
2.6.5.7	Screws for protective bonding		N/A
2.6.5.8	Reliance on telecommunication network or cable distribution system		N/A
2.7	**Overcurrent and earth fault protection in primary circuits**		N/A
2.7.1	Basic requirements	No primary circuits	N/A
	Instructions when protection relies on building installation		N/A
2.7.2	Faults not simulated in 5.3.7		N/A
2.7.3	Short-circuit backup protection		N/A
2.7.4	Number and location of protective devices .....:		N/A
2.7.5	Protection by several devices		N/A
2.7.6	Warning to service personnel .....:		N/A
2.8	**Safety interlocks**		N/A
2.8.1	General principles	No safety interlocks	N/A
2.8.2	Protection requirements		N/A
2.8.3	Inadvertent reactivation		N/A
2.8.4	Fail-safe operation		N/A
	Protection against extreme hazard		N/A
2.8.5	Moving parts		N/A
2.8.6	Overriding		N/A
2.8.7	Switches, relays and their related circuits		N/A
2.8.7.1	Separation distances for contact gaps and their related circuits (mm) .....:		N/A
2.8.7.2	Overload test		N/A
2.8.7.3	Endurance test		N/A
2.8.7.4	Electric strength test		N/A
2.8.8	Mechanical actuators		N/A
2.9	**Electrical insulation**		P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.9.1	Properties of insulating materials		P
2.9.2	Humidity conditioning		N/A
	Relative humidity (%), temperature (°C) .....:		—
2.9.3	Grade of insulation		P
2.9.4	Separation from hazardous voltages		N/A
	Method(s) used .....:		—
2.10	**Clearances, creepage distances and distances through insulation**		N/A
2.10.1	General		N/A
2.10.1.1	Frequency .....:		N/A
2.10.1.2	Pollution degrees .....:		N/A
2.10.1.3	Reduced values for functional insulation		N/A
2.10.1.4	Intervening unconnected conductive parts		N/A
2.10.1.5	Insulation with varying dimensions		N/A
2.10.1.6	Special separation requirements		N/A
2.10.1.7	Insulation in circuits generating starting pulses		N/A
2.10.2	Determination of working voltage		N/A
2.10.2.1	General		N/A
2.10.2.2	RMS working voltage		N/A
2.10.2.3	Peak working voltage		N/A
2.10.3	Clearances		N/A
2.10.3.1	General		N/A
2.10.3.2	Mains transient voltages		N/A
	a) AC mains supply .....:		N/A
	b) Earthed d.c. mains supplies .....:		N/A
	c) Unearthed d.c. mains supplies .....:		N/A
	d) Battery operation .....:		N/A
2.10.3.3	Clearances in primary circuits		N/A
2.10.3.4	Clearances in secondary circuits		N/A
2.10.3.5	Clearances in circuits having starting pulses		N/A
2.10.3.6	Transients from a.c. mains supply .....:		N/A
2.10.3.7	Transients from d.c. mains supply .....:		N/A
2.10.3.8	Transients from telecommunication networks and cable distribution systems .....:		N/A
2.10.3.9	Measurement of transient voltage levels		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	a) Transients from a mains supply		N/A
	For an a.c. mains supply .....:		N/A
	For a d.c. mains supply .....:		N/A
	b) Transients from a telecommunication network :		N/A
2.10.4	Creepage distances		N/A
2.10.4.1	General		N/A
2.10.4.2	Material group and comparative tracking index		N/A
	CTI tests.....:		—
2.10.4.3	Minimum creepage distances		N/A
2.10.5	Solid insulation		N/A
2.10.5.1	General		N/A
2.10.5.2	Distances through insulation		N/A
2.10.5.3	Insulating compound as solid insulation		N/A
2.10.5.4	Semiconductor devices		N/A
2.10.5.5.	Cemented joints		N/A
2.10.5.6	Thin sheet material – General		N/A
2.10.5.7	Separable thin sheet material		N/A
	Number of layers (pcs).....:		—
2.10.5.8	Non-separable thin sheet material		N/A
2.10.5.9	Thin sheet material – standard test procedure		N/A
	Electric strength test		—
2.10.5.10	Thin sheet material – alternative test procedure		N/A
	Electric strength test		—
2.10.5.11	Insulation in wound components		N/A
2.10.5.12	Wire in wound components		N/A
	Working voltage .....:		N/A
	a) Basic insulation not under stress .....:		N/A
	b) Basic, supplementary, reinforced insulation .....:		N/A
	c) Compliance with Annex U .....:		N/A
	Two wires in contact inside wound component; angle between 45° and 90° .....:		N/A
2.10.5.13	Wire with solvent-based enamel in wound components		N/A
	Electric strength test		—
	Routine test		N/A
2.10.5.14	Additional insulation in wound components		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Working voltage .....:		N/A
	- Basic insulation not under stress .....:		N/A
	- Supplementary, reinforced insulation .....:		N/A
2.10.6	Construction of printed boards		N/A
2.10.6.1	Uncoated printed boards		N/A
2.10.6.2	Coated printed boards		N/A
2.10.6.3	Insulation between conductors on the same inner surface of a printed board		N/A
2.10.6.4	Insulation between conductors on different layers of a printed board		N/A
	Distance through insulation		N/A
	Number of insulation layers (pcs) .....:		N/A
2.10.7	Component external terminations		N/A
2.10.8	Tests on coated printed boards and coated components		N/A
2.10.8.1	Sample preparation and preliminary inspection		N/A
2.10.8.2	Thermal conditioning		N/A
2.10.8.3	Electric strength test		N/A
2.10.8.4	Abrasion resistance test		N/A
2.10.9	Thermal cycling		N/A
2.10.10	Test for Pollution Degree 1 environment and insulating compound		N/A
2.10.11	Tests for semiconductor devices and cemented joints		N/A
2.10.12	Enclosed and sealed parts		N/A

3	**WIRING, CONNECTIONS AND SUPPLY**		
3.1	**General**		P
3.1.1	Current rating and overcurrent protection		P
3.1.2	Protection against mechanical damage		P
3.1.3	Securing of internal wiring		P
3.1.4	Insulation of conductors		N/A
3.1.5	Beads and ceramic insulators		N/A
3.1.6	Screws for electrical contact pressure		N/A
3.1.7	Insulating materials in electrical connections		N/A
3.1.8	Self-tapping and spaced thread screws		N/A
3.1.9	Termination of conductors		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	10 N pull test		N/A
3.1.10	Sleeving on wiring		N/A
3.2	**Connection to a mains supply**		N/A
3.2.1	Means of connection		N/A
3.2.1.1	Connection to an a.c. mains supply		N/A
3.2.1.2	Connection to a d.c. mains supply		N/A
3.2.2	Multiple supply connections		N/A
3.2.3	Permanently connected equipment		N/A
	Number of conductors, diameter of cable and conduits (mm) ..... :		—
3.2.4	Appliance inlets		N/A
3.2.5	Power supply cords		N/A
3.2.5.1	AC power supply cords		N/A
	Type ..... :		—
	Rated current (A), cross-sectional area (mm^2), AWG ..... :		—
3.2.5.2	DC power supply cords		N/A
3.2.6	Cord anchorages and strain relief		N/A
	Mass of equipment (kg), pull (N) ..... :		—
	Longitudinal displacement (mm) ..... :		—
3.2.7	Protection against mechanical damage		N/A
3.2.8	Cord guards		N/A
	Diameter or minor dimension D (mm); test mass (g) ..... :		—
	Radius of curvature of cord (mm)..... :		—
3.2.9	Supply wiring space		N/A
3.3	**Wiring terminals for connection of external conductors**		N/A
3.3.1	Wiring terminals		N/A
3.3.2	Connection of non-detachable power supply cords		N/A
3.3.3	Screw terminals		N/A
3.3.4	Conductor sizes to be connected		N/A
	Rated current (A), cord/cable type, cross-sectional area (mm^2)..... :		—
3.3.5	Wiring terminal sizes		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Rated current (A), type, nominal thread diameter (mm) ..... :		—
3.3.6	Wiring terminal design		N/A
3.3.7	Grouping of wiring terminals		N/A
3.3.8	Stranded wire		N/A
3.4	**Disconnection from the mains supply**		N/A
3.4.1	General requirement	Not directly connected to mains supply	N/A
3.4.2	Disconnect devices		N/A
3.4.3	Permanently connected equipment		N/A
3.4.4	Parts which remain energized		N/A
3.4.5	Switches in flexible cords		N/A
3.4.6	Number of poles – single-phase and d.c. equipment		N/A
3.4.7	Number of poles – three-phase equipment		N/A
3.4.8	Switches as disconnect devices		N/A
3.4.9	Plugs as disconnect devices		N/A
3.4.10	Interconnected equipment		N/A
3.4.11	Multiple power sources		N/A
3.5	**Interconnection of equipment**		P
3.5.1	General requirements		P
3.5.2	Types of interconnection circuits ..... :	SELV circuit only	P
3.5.3	ELV circuits as interconnection circuits	No ELV circuits	N/A
3.5.4	Data ports for additional equipment		N/A
4	**PHYSICAL REQUIREMENTS**		
4.1	**Stability**		N/A
	Angle of 10°		N/A
	Test force (N) .....:		N/A
4.2	**Mechanical strength**		P
4.2.1	General		P
	Rack-mounted equipment.		N/A
4.2.2	Steady force test, 10 N	No damage, no hazard	P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.2.3	Steady force test, 30 N		N/A
4.2.4	Steady force test, 250 N	No damage, no hazard	P
4.2.5	Impact test		N/A
	Fall test		N/A
	Swing test		N/A
4.2.6	Drop test; height (mm) .....:	1m, damage, no hazard/	P
4.2.7	Stress relief test	70°C, 7h	P
4.2.8	Cathode ray tubes		N/A
	Picture tube separately certified .....:		N/A
4.2.9	High pressure lamps		N/A
4.2.10	Wall or ceiling mounted equipment; force (N) .....:		N/A
4.3	**Design and construction**		P
4.3.1	Edges and corners	No sharp edges or comers	P
4.3.2	Handles and manual controls; force (N).....:		N/A
4.3.3	Adjustable controls		N/A
4.3.4	Securing of parts		P
4.3.5	Connection by plugs and sockets		N/A
4.3.6	Direct plug-in equipment		N/A
	Torque .....:		—
	Compliance with the relevant mains plug standard .....:		N/A
4.3.7	Heating elements in earthed equipment		N/A
4.3.8	Batteries		P
	- Overcharging of a rechargeable battery		P
	- Unintentional charging of a non-rechargeable battery		N/A
	- Reverse charging of a rechargeable battery		P
	- Excessive discharging rate for any battery		P
4.3.9	Oil and grease		N/A
4.3.10	Dust, powders, liquids and gases	No dust, powders, liquids and gases.	N/A
4.3.11	Containers for liquids or gases	No containers for liquid and gases.	N/A
4.3.12	Flammable liquids .....:	No flammable liquid.	N/A
	Quantity of liquid (l) .....:		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Flash point (°C) .....:		N/A
4.3.13	Radiation		P
4.3.13.1	General		P
4.3.13.2	Ionizing radiation		N/A
	Measured radiation (pA/kg) .....:		—
	Measured high-voltage (kV) .....:		—
	Measured focus voltage (kV) .....:		—
	CRT markings .....:		—
4.3.13.3	Effect of ultraviolet (UV) radiation on materials		N/A
	Part, property, retention after test, flammability classification .....:		N/A
4.3.13.4	Human exposure to ultraviolet (UV) radiation .....:		N/A
4.3.13.5	Lasers (including laser diodes) and LEDs		P
4.3.13.5.1	Lasers (including laser diodes)		N/A
	Laser class .....:		—
4.3.13.5.2	Light emitting diodes (LEDs)	LED used as indicator only.	P
4.3.13.6	Other types .....:		N/A

4.4	**Protection against hazardous moving parts**		N/A
4.4.1	General		N/A
4.4.2	Protection in operator access areas ..... :		N/A
	Household and home/office document/media shredders		N/A
4.4.3	Protection in restricted access locations ..... :		N/A
4.4.4	Protection in service access areas		N/A
4.4.5	Protection against moving fan blades		N/A
4.4.5.1	General		N/A
	Not considered to cause pain or injury. A)……:		N/A
	Is considered to cause pain, not injury. B) ……...:		N/A
	Considered to cause injury. C) ……:		N/A
4.4.5.2	Protection for users		N/A
	Use of symbol or warning ……..:		N/A
4.4.5.3	Protection for service persons		N/A
	Use of symbol or warning ……..:		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.5	**Thermal requirements**		P
4.5.1	General		P
4.5.2	Temperature tests		P
	Normal load condition per Annex L ..... :	(see appended table 4.5)	—
4.5.3	Temperature limits for materials	(see appended table 4.5)	P
4.5.4	Touch temperature limits	(see appended table 4.5)	P
4.5.5	Resistance to abnormal heat ..... :		N/A
4.6	**Openings in enclosures**		N/A
4.6.1	Top and side openings		N/A
	Dimensions (mm) ..... :		—
4.6.2	Bottoms of fire enclosures	No openings	N/A
	Construction of the bottomm, dimensions (mm) .. :		—
4.6.3	Doors or covers in fire enclosures		N/A
4.6.4	Openings in transportable equipment		N/A
4.6.4.1	Constructional design measures		N/A
	Dimensions (mm) ..... :		—
4.6.4.2	Evaluation measures for larger openings		N/A
4.6.4.3	Use of metallized parts		N/A
4.6.5	Adhesives for constructional purposes		N/A
	Conditioning temperature (°C), time (weeks) ..... :		—
4.7	**Resistance to fire**		P
4.7.1	Reducing the risk of ignition and spread of flame		P
	Method 1, selection and application of components wiring and materials	(see appended table 4.7)	P
	Method 2, application of all of simulated fault condition tests		N/A
4.7.2	Conditions for a fire enclosure		P
4.7.2.1	Parts requiring a fire enclosure		P
4.7.2.2	Parts not requiring a fire enclosure		N/A
4.7.3	Materials		P
4.7.3.1	General	PCB: min. V-1	P
4.7.3.2	Materials for fire enclosures	Plastic enclosure: min. V-1	P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.7.3.3	Materials for components and other parts outside fire enclosures		N/A
4.7.3.4	Materials for components and other parts inside fire enclosures	Min. V-2	P
4.7.3.5	Materials for air filter assemblies		N/A
4.7.3.6	Materials used in high-voltage components		N/A
5	**ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS**		
5.1	**Touch current and protective conductor current**		N/A
5.1.1	General		N/A
5.1.2	Configuration of equipment under test (EUT)		N/A
5.1.2.1	Single connection to an a.c. mains supply		N/A
5.1.2.2	Redundant multiple connections to an a.c. mains supply		N/A
5.1.2.3	Simultaneous multiple connections to an a.c. mains supply		N/A
5.1.3	Test circuit		N/A
5.1.4	Application of measuring instrument		N/A
5.1.5	Test procedure		N/A
5.1.6	Test measurements		N/A
	Supply voltage (V) .....:		—
	Measured touch current (mA) .....:		—
	Max. allowed touch current (mA) .....:		—
	Measured protective conductor current (mA) .....:		—
	Max. allowed protective conductor current (mA)...:		—
5.1.7	Equipment with touch current exceeding 3,5 mA		N/A
5.1.7.1	General .....:		N/A
5.1.7.2	Simultaneous multiple connections to the supply		N/A
5.1.8	Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks		N/A
5.1.8.1	Limitation of the touch current to a telecommunication network or to a cable distribution system		N/A
	Supply voltage (V) .....:		—
	Measured touch current (mA) .....:		—
	Max. allowed touch current (mA) .....:		—

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.1.8.2	Summation of touch currents from telecommunication networks		N/A
	a) EUT with earthed telecommunication ports .....:		N/A
	b) EUT whose telecommunication ports have no reference to protective earth		N/A
5.2	**Electric strength**		N/A
5.2.1	General		N/A
5.2.2	Test procedure		N/A
5.3	**Abnormal operating and fault conditions**		P
5.3.1	Protection against overload and abnormal operation		P
5.3.2	Motors		P
5.3.3	Transformers		N/A
5.3.4	Functional insulation.....:	By short circuit	P
5.3.5	Electromechanical components		N/A
5.3.6	Audio amplifiers in ITE .....:		P
5.3.7	Simulation of faults	(see appended table 5.3)	P
5.3.8	Unattended equipment		N/A
5.3.9	Compliance criteria for abnormal operating and fault conditions		P
5.3.9.1	During the tests		P
5.3.9.2	After the tests		P
6	**CONNECTION TO TELECOMMUNICATION NETWORKS**		
6.1	**Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment**		N/A
6.1.1	Protection from hazardous voltages		N/A
6.1.2	Separation of the telecommunication network from earth		N/A
6.1.2.1	Requirements		N/A
	Supply voltage (V) .....:		—
	Current in the test circuit (mA) .....:		—
6.1.2.2	Exclusions .....:		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

6.2	**Protection of equipment users from overvoltages on telecommunication networks**		N/A
6.2.1	Separation requirements		N/A
6.2.2	Electric strength test procedure		N/A
6.2.2.1	Impulse test		N/A
6.2.2.2	Steady-state test		N/A
6.2.2.3	Compliance criteria		N/A

6.3	**Protection of the telecommunication wiring system from overheating**		N/A
	Max. output current (A) .....:		—
	Current limiting method .....:		—

7	**CONNECTION TO CABLE DISTRIBUTION SYSTEMS**		
7.1	**General**		N/A
7.2	Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment		N/A
7.3	Protection of equipment users from overvoltages on the cable distribution system		N/A
7.4	Insulation between primary circuits and cable distribution systems		N/A
7.4.1	General		N/A
7.4.2	Voltage surge test		N/A
7.4.3	Impulse test		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

A	**ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE**		
A.1	**Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2)**		N/A
A.1.1	Samples.....:		—
	Wall thickness (mm) .....:		—
A.1.2	Conditioning of samples; temperature (°C) .....:		N/A
A.1.3	Mounting of samples .....:		N/A
A.1.4	Test flame (see IEC 60695-11-3)		N/A
	Flame A, B, C or D .....:		—
A.1.5	Test procedure		N/A
A.1.6	Compliance criteria		N/A
	Sample 1 burning time (s) .....:		—
	Sample 2 burning time (s) .....:		—
	Sample 3 burning time (s) .....:		—
A.2	**Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4)**		N/A
A.2.1	Samples, material.....:		—
	Wall thickness (mm) .....:		—
A.2.2	Conditioning of samples; temperature (°C) .....:		N/A
A.2.3	Mounting of samples .....:		N/A
A.2.4	Test flame (see IEC 60695-11-4)		N/A
	Flame A, B or C .....:		—
A.2.5	Test procedure		N/A
A.2.6	Compliance criteria		N/A
	Sample 1 burning time (s) .....:		—
	Sample 2 burning time (s) .....:		—
	Sample 3 burning time (s) .....:		—
A.2.7	Alternative test acc. To IEC 60695-11-5, cl. 5 and 9		N/A
	Sample 1 burning time (s) .....:		—
	Sample 2 burning time (s) .....:		—
	Sample 3 burning time (s) .....:		—
A.3	**Hot flaming oil test (see 4.6.2)**		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
A.3.1	Mounting of samples		N/A
A.3.2	Test procedure		N/A
A.3.3	Compliance criterion		N/A
B	**ANNEX B, MOTOR TESTS UNDER ABNORMAL CONDITIONS (see 4.7.2.2 and 5.3.2)**		
B.1	**General requirements**		P
	Position .....:		—
	Manufacturer .....:		—
	Type .....:		—
	Rated values .....:		—
B.2	**Test conditions**		N/A
B.3	**Maximum temperatures**		N/A
B.4	**Running overload test**		N/A
B.5	**Locked-rotor overload test**		N/A
	Test duration (days) .....:		—
	Electric strength test: test voltage (V) .....:		—
B.6	**Running overload test for d.c. motors in secondary circuits**		N/A
B.6.1	General		N/A
B.6.2	Test procedure		N/A
B.6.3	Alternative test procedure		N/A
B.6.4	Electric strength test; test voltage (V) .....:		N/A
B.7	**Locked-rotor overload test for d.c. motors in secondary circuits**		P
B.7.1	General		P
B.7.2	Test procedure		P
B.7.3	Alternative test procedure		P
B.7.4	Electric strength test; test voltage (V) .....:		P
B.8	**Test for motors with capacitors**		N/A
B.9	**Test for three-phase motors**		N/A
B.10	**Test for series motors**		N/A
	Operating voltage (V) .....:		—
C	**ANNEX C, TRANSFORMERS (see 1.5.4 and 5.3.3)**		
	Position .....:		—

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Manufacturer .....:		—
	Type .....:		—
	Rated values .....:		—
	Method of protection..... :		—
C.1	**Overload test**		N/A
C.2	**Insulation**		N/A
	Protection from displacement of windings..... :		N/A
D	**ANNEX D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS (see 5.1.4)**		
D.1	**Measuring instrument**		N/A
D.2	**Alternative measuring instrument**		N/A
E	**ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13)**		N/A
F	**ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10 and Annex G)**		N/A
G	**ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES**		
G.1	**Clearances**		N/A
G.1.1	General		N/A
G.1.2	Summary of the procedure for determining minimum clearances		N/A
G.2	**Determination of mains transient voltage (V)**		N/A
G.2.1	AC mains supply .....:		N/A
G.2.2	Earthed d.c. mains supplies .....:		N/A
G.2.3	Unearthed d.c. mains supplies .....:		N/A
G.2.4	Battery operation .....:		N/A
G.3	**Determination of telecommunication network transient voltage (V) ..... :**		N/A
G.4	**Determination of required withstand voltage (V)**		N/A
G.4.1	Mains transients and internal repetitive peaks .....:		N/A
G.4.2	Transients from telecommunication networks .....:		N/A
G.4.3	Combination of transients		N/A
G.4.4	Transients from cable distribution systems		N/A
G.5	**Measurement of transient voltages (V)**		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	a) Transients from a mains supply		N/A
	For an a.c. mains supply		N/A
	For a d.c. mains supply		N/A
	b) Transients from a telecommunication network		N/A
G.6	**Determination of minimum clearances ..... :**		N/A
H	**ANNEX H, IONIZING RADIATION (see 4.3.13)**		N/A
J	**ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)**		N/A
	Metal(s) used .....:		—
K	**ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.8)**		
K.1	Making and breaking capacity		N/A
K.2	Thermostat reliability; operating voltage (V) .....:		N/A
K.3	Thermostat endurance test; operating voltage (V) .....:		N/A
K.4	Temperature limiter endurance; operating voltage (V) .....:		N/A
K.5	Thermal cut-out reliability		N/A
K.6	Stability of operation		N/A
L	**ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.2)**		
L.1	Typewriters		N/A
L.2	Adding machines and cash registers		N/A
L.3	Erasers		N/A
L.4	Pencil sharpeners		N/A
L.5	Duplicators and copy machines		N/A
L.6	Motor-operated files		N/A
L.7	Other business equipment		P
M	**ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)**		
M.1	Introduction		N/A
M.2	Method A		N/A
M.3	Method B		N/A
M.3.1	Ringing signal		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.3.1.1	Frequency (Hz) .....:		—
M.3.1.2	Voltage (V) .....:		—
M.3.1.3	Cadence; time (s), voltage (V) .....:		—
M.3.1.4	Single fault current (mA) .....:		—
M.3.2	Tripping device and monitoring voltage .....:		N/A
M.3.2.1	Conditions for use of a tripping device or a monitoring voltage		N/A
M.3.2.2	Tripping device		N/A
M.3.2.3	Monitoring voltage (V) .....:		N/A
N	**ANNEX N, IMPULSE TEST GENERATORS (see 1.5.7.2, 1.5.7.3, 2.10.3.9, 6.2.2.1, 7.3.2, 7.4.3 and Clause G.5)**		
N.1	ITU-T impulse test generators		N/A
N.2	IEC 60065 impulse test generator		N/A
P	**ANNEX P, NORMATIVE REFERENCES**		—
Q	**ANNEX Q, Voltage dependent resistors (VDRs) (see 1.5.9.1)**		
	- Preferred climatic categories .....:		N/A
	- Maximum continuous voltage .....:		N/A
	- Combination pulse current .....:		N/A
	Body of the VDR Test according to IEC60695-11-5.....:		N/A
	Body of the VDR. Flammability class of material (min V-1).....:		N/A
R	**ANNEX R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES**		
R.1	Minimum separation distances for unpopulated coated printed boards (see 2.10.6.2)		N/A
R.2	Reduced clearances (see 2.10.3)		N/A
S	**ANNEX S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3)**		
S.1	Test equipment		N/A
S.2	Test procedure		N/A
S.3	Examples of waveforms during impulse testing		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
T	**ANNEX T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)**		N/A
			—
U	**ANNEX U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION (see 2.10.5.4)**		N/A
			—
V	**ANNEX V, AC POWER DISTRIBUTION SYSTEMS (see 1.6.1)**		
V.1	Introduction		N/A
V.2	TN power distribution systems		N/A
W	**ANNEX W, SUMMATION OF TOUCH CURRENTS**		
W.1	Touch current from electronic circuits		N/A
W.1.1	Floating circuits		N/A
W.1.2	Earthed circuits		N/A
W.2	Interconnection of several equipments		N/A
W.2.1	Isolation		N/A
W.2.2	Common return, isolated from earth		N/A
W.2.3	Common return, connected to protective earth		N/A
X	**ANNEX X, MAXIMUM HEATING EFFECT IN TRANSFORMER TESTS (see clause C.1)**		
X.1	Determination of maximum input current		N/A
X.2	Overload test procedure		N/A
Y	**ANNEX Y, ULTRAVIOLET LIGHT CONDITIONING TEST (see 4.3.13.3)**		
Y.1	Test apparatus .....:		N/A
Y.2	Mounting of test samples .....:		N/A
Y.3	Carbon-arc light-exposure apparatus .....:		N/A
Y.4	Xenon-arc light exposure apparatus .....:		N/A
Z	**ANNEX Z, OVERVOLTAGE CATEGORIES (see 2.10.3.2 and Clause G.2)**		N/A
AA	**ANNEX AA, MANDREL TEST (see 2.10.5.8)**		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

BB	**ANNEX BB, CHANGES IN THE SECOND EDITION**	—

CC	**ANNEX CC, Evaluation of integrated circuit (IC) current limiters**		
CC.1	General		N/A
CC.2	Test program 1……:		N/A
CC.3	Test program 2……:		N/A
CC.4	Test program 3.....:		N/A
CC.5	Compliance.....:		N/A

DD	**ANNEX DD, Requirements for the mounting means of rack-mounted equipment**		
DD.1	General		N/A
DD.2	Mechanical strength test, variable N……..:		N/A
DD.3	Mechanical strength test, 250N, including end stops……:		N/A
DD.4	Compliance……:		N/A

EE	**ANNEX EE, Household and home/office document/media shredders**		
EE.1	General		N/A
EE.2	Markings and instructions		N/A
	Use of markings or symbols……:		N/A
	Information of user instructions, maintenance and/or servicing instructions……:		N/A
EE.3	Inadvertent reactivation test……:		N/A
EE.4	Disconnection of power to hazardous moving parts:		N/A
	Use of markings or symbols……:		N/A
EE.5	Protection against hazardous moving parts		N/A
	Test with test finger (Figure 2A) ……:		N/A
	Test with wedge probe (Figure EE1 and EE2) ……:		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.5.1	TABLE: List of critical components				P
Object/part No.	Manufacturer/ trademark	Type/model	Technical data	Standard (Edition / year)	Mark(s) of conformity[1])
Plastic enclosure	Chang Chun Sb(Changshu) Co., Ltd.	EME-5051	V-0, 130°C	UL 94, UL 746	UL E223871
PCB	Interchangeable	Interchangeable	Min. V-1, 130°C.	UL 796	UL
Battery	Rechargeable Li-ion Battery	BAT17M15580	3.8V 5580mAh	EN62133: 2013	LCS1711221035AS
Motor	SHENZHEN HONGZHIFA Machinery&Electronics CO.,LTD	HZF-Z04HB-RTB20	3.0VDC/85mA Max.	EN60950-1	Test with appliance
Internal wire	Interchangeable	Interchangeable	300V, 20AWG, 80°C	UL 758	UL
ADAPTER	SHEN ZHEN HUAJIN ELECTRONICS CO., LTD	HJ-FC016K7-EU	Input: 100-240V~, 50/60Hz,0.6A; Output: 5V⎓, 3000mA/7V⎓, 3000mA/9V⎓, 2700mA/12V⎓, 2000mA	EN 60950-1: 2006+A11: 2009+A1: 2010+A12: 2011+A2: 2013	Shenzhen Hongcai Testing Co., Ltd. HCT17FR-0943S
SPEAKER	Keysounds	QS151130EL22	3W/4Ω	EN 60950-1	Tested with appliance
Supplementary information: [1]) Provided evidence ensures the agreed level of compliance.					

1.5.1	TABLE: Opto Electronic Devices				N/A
Manufacturer..... :	--	--	--	--	
Type..... :	--	--	--	--	
Separately tested..... :	--	--	--	--	
Bridging insulation ..... :	--	--	--	--	
External creepage distance ..... :	--	--	--	--	
Internal creepage distance ..... :	--	--	--	--	
Distance through insulation ..... :	--	--	--	--	

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Tested under the following conditions ..... :	--	--	--	--
Input ..... :	--	--	--	--
Output ..... :	--	--	--	--
supplementary information				

1.6.2	TABLE: Electrical data (in normal conditions)					P
U (Vd.c.)	I (A)	Irated (A)	P (W)	Fuse #	Ifuse (A)	Condition/status
7	2.5	3	17.5	--	--	EUT charging and normal working
9	2	2.7	18	--	--	EUT charging and normal working
12	1.6	2	19.2	--	--	EUT charging and normal working
Supplementary information:						

2.1.1.5 c) 1)	TABLE: max. V, A, VA test				N/A
Voltage (rated) (V)	Current (rated) (A)	Voltage (max.) (V)	Current (max.) (A)	VA (max.) (VA)	
--	--	--	--	--	
Supplementary information:					

2.1.1.5 c) 2)	TABLE: stored energy	N/A
Capacitance C (µF)	Voltage U (V)	Energy E (J)
-	-	-
supplementary information:		

2.2	TABLE: evaluation of voltage limiting components in SELV circuits		N/A
Component (measured between)	max. voltage (V) (normal operation)		Voltage Limiting Components
	V peak	V d.c.	
--	--	--	--
Fault test performed on voltage limiting components	Voltage measured (V) in SELV circuits (V peak or V d.c.)		

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

supplementary information:
SC: short-circuit

2.5	TABLE: Limited power sources	P

Circuit output tested:

Note: Measured Uoc (V) with all load circuits disconnected:

Components	Sample No.	Uoc (V)	I_{sc} (A)		VA	
			Meas.	Limit	Meas.	Limit
Normal	--	4.3	3.8	8	14.85	100
D1 S-C	--	0	0	8	0	100

supplementary information:
Under normal and fault conditions, the worst case was recorded.

SC=short-circuit, OC=open-circuit

2.10.2	Table: working voltage measurement	N/A

Location	RMS voltage (V)	Peak voltage (V)	Comments
--	--	--	--
--	--	--	--

supplementary information:

2.10.3 and 2.10.4	TABLE: Clearance and creepage distance measurements	N/A

Clearance (cl) and creepage distance (cr) at/of/between:	U peak (V)	U r.m.s. (V)	Required cl (mm)	cl (mm)	Required cr (mm)	cr (mm)
Functional:						
--	--	--	--	--	--	--
Basic/supplementary:						
--	--	--	--	--	--	--
Reinforced:						
--	--	--	--	--	--	--
Supplementary information:						

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

2.10.5	TABLE: Distance through insulation measurements					N/A
Distance through insulation (DTI) at/of:		U peak (V)	U rms (V)	Test voltage (Vac)	Required DTI (mm)	DTI (mm)
--		--	--	--	--	--
Remark:						

4.3.8	TABLE: Batteries (see appended table 5.3)								P
The tests of 4.3.8 are applicable only when appropriate battery data is not available									P
Is it possible to install the battery in a reverse polarity position?									P
	Non-rechargeable batteries			Rechargeable batteries					
	Discharging		Un-intentional charging	Charging		Discharging		Reversed charging	
	Meas. current	Manuf. Specs.		Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.	Meas. current	Manuf. Specs.
Max. current during normal condition	--	--	--	3870 mA	5580 mA	3910 mA	5580 mA	--	--
Max. current during fault condition	--	--	--	4250 mA	5580 mA	4270 mA	5580 mA	--	--
Test results:									Verdict
- Chemical leaks									P
- Explosion of the battery									P
- Emission of flame or expulsion of molten metal									P
- Electric strength tests of equipment after completion of tests									N/A
Supplementary information:									

4.3.8	TABLE: Batteries	P

Battery category	:	Li-Polymer
Manufacturer	:	See table 1.5.1
Type / model	:	See table 1.5.1
Voltage	:	3.8V
Capacity	:	5580mAh
Tested and Certified by (incl. Ref. No.)	:	See table 1.5.1

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Circuit protection diagram:	--

MARKINGS AND INSTRUCTIONS (1.7.13)	
Location of replaceable battery	
Language(s) ……:	
Close to the battery ……:	
In the servicing instructions ……:	
In the operating instructions ……:	

4.5	TABLE: Thermal requirements(7Vdc, 3A)			P
	Supply voltage (V) .....:	Battery discharging	charging	—
	Ambient T_{min} (°C) .....:	40.0	40.0	—
	Ambient T_{max} (°C) .....:	40.1	40.1	—
Maximum measured temperature T of part/at…..:		T (°C)		Allowed T_{max} (°C)
Internal wire		50.6	51.2	80
PCB near U1		62.8	63.5	130
C1		64.2	65.1	105
PCB near R1		63.5	62.7	130
Battery		55.2	54.8	60
Adaptor Enclosure		45.6	46.2	Ref.
Enclosure inside		47.6	48.1	130
Enclosure outside		42.3	41.7	75

Supplementary information:
The maximum operating temperature is 40ºC.
Temperature measurement was carried out on the most unfavourable test condition.

Temperature T of winding:	t_1 (°C)	R_1 (Ω)	t_2 (°C)	R_2 (Ω)	T (°C)	Allowed T_{max} (°C)	Insulation class
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--

Supplementary information:

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

4.5	TABLE: Thermal requirements(9Vdc, 2.7A)			P
	Supply voltage (V) .....:	Battery discharging	charging	—
	Ambient T_{min} (°C) .....:	40.0	40.0	—
	Ambient T_{max} (°C) .....:	40.1	40.1	—
Maximum measured temperature T of part/at…..:		T (°C)		Allowed T_{max} (°C)
Internal wire		52.9	53.4	80
PCB near U1		64.8	62.3	130
C1		63.4	60.8	105
PCB near R1		60.8	59.4	130
Battery		52.6	50.6	60
Adaptor Enclosure		45.8	48.2	Ref.
Enclosure inside		47.7	46.8	130
Enclosure outside		42.6	43.1	75

Supplementary information:
The maximum operating temperature is 40ºC.
Temperature measurement was carried out on the most unfavourable test condition.

Temperature T of winding:	t_1 (°C)	R_1 (Ω)	t_2 (°C)	R_2 (Ω)	T (°C)	Allowed T_{max} (°C)	Insulation class
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--

Supplementary information:

4.5	TABLE: Thermal requirements(12Vdc, 2A)			P
	Supply voltage (V) .....:	Battery discharging	charging	—
	Ambient T_{min} (°C) .....:	40.0	40.0	—
	Ambient T_{max} (°C) .....:	40.1	40.1	—
Maximum measured temperature T of part/at…..:		T (°C)		Allowed T_{max} (°C)
Internal wire		54.1	57.9	80
PCB near U1		63.5	62.4	130
C1		62.7	63.6	105
PCB near R1		60.8	62.4	130
Battery		53.7	54.7	60
Adaptor Enclosure		55.6	56.8	Ref.
Enclosure inside		51.6	52.1	130

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Enclosure outside	42.4	42.6	75

Supplementary information:
The maximum operating temperature is 40ºC.
Temperature measurement was carried out on the most unfavourable test condition.

Temperature T of winding:	t_1 (°C)	R_1 (Ω)	t_2 (°C)	R_2 (Ω)	T (°C)	Allowed T_{max} (°C)	Insulation class
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--

Supplementary information:

4.5.5	TABLE: Ball pressure test of thermoplastic parts		N/A
	Allowed impression diameter (mm) .....:	≤ 2 mm	—

Part	Test temperature (°C)	Impression diameter (mm)
--	--	--

Supplementary information:

4.7	TABLE: Resistance to fire					P
Part	Manufacturer of material	Type of material	Thickness (mm)	Flammability class	Evidence	
--	--	--	--	--	--	

supplementary information: Refer to table 1.5.1 for details.

5.1	TABLE: touch current measurement		N/A
Measured between:	Measured (mA)	Limit (mA)	Comments/conditions
--	--	--	--

supplementary information:

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

5.2	TABLE: Electric strength tests, impulse tests and voltage surge tests			N/A
Test voltage applied between:		Voltage shape (AC, DC, impulse, surge)	Test voltage (V)	Breakdown Yes / No
Functional:				
--		--	--	--
Basic/supplementary:				
--		--	--	--
Reinforced:				
--		--	--	--
Supplementary information:				

5.3	TABLE: Fault condition tests		P
	Ambient temperature (°C) ..... :	25°C, unless otherwise specified	—
	Power source for EUT: Manufacturer, model/type, output rating ..... :	-	—

Component No.	Fault	Supply voltage (V)	Test time	Fuse	Fuse current (A)	Observation
C1	S-C	12V⎓	10mins	--	--	The power is decrease to 0.12W immediately, Recoverable, no hazard.
R1	S-C	2V⎓	10mins	--	--	The power is decrease to 0.14W immediately, Recoverable, no hazard.
Motor	Locked	12V⎓	7h17mins	--	--	The unit working normally, IC: 79.2℃,ambient: 40.1℃, no hazards
Battery	O-C	3.8V⎓	7h26mins	--	--	The power is decrease to 0.14W immediately, Recoverable, No hazard.
Battery	E-D	--	7h18mins	--	--	The power is decrease to 0.12W immediately, Recoverable, No hazard.
Battery B+ to B-	S-C	--	10mins	--	--	The battery is not cause fire or explosion, and the temperature of EUT is normal, No hazard.

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

IEC 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

Component No.	Fault	Supply voltage (V)	Test time	Fuse	Fuse current (A)	Observation
Battery	O-C (D5(on PCB of battery)S-C)	3.8V⎓	8h32mins	--	--	Unit shutdown immediately, and battery cannot charging, Recoverable, No hazard.
Battery	E-D (D5(on PCB of battery)S-C)	--	8h34mins	--	--	When the battery output voltage are 2.0V, Battery were protected, No hazard.
Speaker	S-C	12V⎓	10mins	--	--	Input power decreased to 0.12W immediately. Recoverable. No hazard.
Speaker	max. non-clipped	12V⎓	3h55mins	--	--	Unit working normal, No evident temperature rise, No hazard.

Supplementary information:

1. SC: short-circuit; OC: open-circuit; OL: overload;
2. SELV outputs did not exceed 42.4Vpeak or 60Vdc for longer than 0.2 secs and did not exceed the limit of 71Vpeak or 120Vpeak after abnormal tests were applied.

C.2	TABLE: transformers	N/A

Loc.	Tested insulation	Working voltage peak / V (2.10.2)	Working voltage rms / V (2.10.2)	Required electric strength (5.2)	Required clearance / mm (2.10.3)	Required creepage distance / mm (2.10.4)	Required distance thr. insul. (2.10.5)
--	--	--	--	--	--	--	--
Loc.	Tested insulation			Test voltage/ V	Measured clearance / mm	Measured creepage dist./ mm	Measured distance thr. insul. / mm; number of layers
--	--	--	--	--	--	--	--
supplementary information:							

C.2	TABLE: Transformer	N/A
Winding diagram:		

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ATTACHMENT TO TEST REPORT IEC 60950-1
EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES

Information technology equipment – Safety –

Part 1: General requirements

Differences according to.....:	EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013
Attachment Form No.....:	EU_GD_IEC60950_1F
Attachment Originator .....:	SGS Fimko Ltd
Master Attachment.....:	Date 2014-02

Copyright © 2014 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.

EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013 – CENELEC COMMON MODIFICATIONS

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	Clauses, subclauses, notes, tables and figures which are additional to those in IEC60950-1 and it´s amendmets are prefixed “Z”		--
Contents (A2:2013)	Add the following annexes: Annex ZA (normative) Normative references to international publications with their corresponding European publications Annex ZB (normative) Special national conditions Annex ZD (informative) IEC and CENELEC code designations for flexible cords		P
General	Delete all the “country” notes in the reference document (IEC 60950-1:2005) according to the following list: 1.4.8 Note 2 1.5.1 Note 2 & 3 1.5.7.1 Note 1.5.8 Note 2 1.5.9.4 Note 1.7.2.1 Note 4, 5 & 6 2.2.3 Note 2.2.4 Note 2.3.2 Note 2.3.2.1 Note 2 2.3.4 Note 2 2.6.3.3 Note 2 & 3 2.7.1 Note 2.10.3.2 Note 2 2.10.5.13 Note 3 3.2.1.1 Note 3.2.4 Note 3. 2.5.1 Note 2 4.3.6 Note 1 & 2 4.7 Note 4 4.7.2.2 Note 4.7.3.1Note 2 5.1.7.1 Note 3 & 4 5.3.7 Note 1 6 Note 2 & 5 6.1.2.1 Note 2 6.1.2.2 Note 6.2.2 Note 6.2.2.1 Note 2 6.2.2.2 Note 7.1 Note 3 7.2 Note 7.3 Note 1 & 2 G.2.1 Note 2 Annex H Note 2		P
General (A1:2010)	Delete all the “country” notes in the reference document (IEC 60950-1:2005/A1:2010) according to the following list: 1.5.7.1 Note 6.1.2.1 Note 2 6.2.2.1 Note 2 EE.3 Note		P
General (A2:2013)	Delete all the “country” notes in the reference document (IEC 60950-1:2005/A2:2013) according to the following list: 2.7.1 Note * 2.10.3.1 Note 2 6.2.2. Note * Note of secretary: Text of Common Modification remains unchanged.		P
1.1.1 (A1:2010)	**Replace** the text of NOTE 3 by the following. NOTE 3 The requirements of EN 60065 may also be used to meet safety requirements for multimedia equipment. See IEC Guide 112, Guide on the safety of multimedia equipment. For television sets EN 60065 applies.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
1.3.Z1	Add the following subclause: 1.3.Z1 Exposure to excessive sound pressure The apparatus shall be so designed and constructed as to present no danger when used for its intended purpose, either in normal operating conditions or under fault conditions, particularly providing protection against exposure to excessive sound pressures from headphones or earphones. NOTE Z1 A new method of measurement is described in EN 50332-1, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 1: General method for "one package equipment", and in EN 50332-2, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 2: Guidelines to associate sets with headphones coming from different manufacturers.		N/A
(A12:2011)	In EN 60950-1:2006/A12:2011 Delete the addition of 1.3.Z1 / EN 60950-1:2006 Delete the definition 1.2.3.Z1 / EN 60950-1:2006 /A1:2010		N/A
1.5.1 (Added info*)	Add the following NOTE: NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2002/95/EC. New Directive 2011/65/11 *		N/A
1.7.2.1 (A1:2010)	In addition, for a PORTABLE SOUND SYSTEM, the instructions shall include a warning that excessive sound pressure from earphones and headphones can cause hearing loss.		N/A
1.7.2.1 (A12.2011)	In EN 60950-1:2006/A12:2011 Delete NOTE Z1 and the addition for Portable Sound System. Add the following clause and annex to the existing standard and amendments.		N/A
	Zx Protection against excessive sound pressure from personal music players		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.1 General This sub-clause specifies requirements for protection against excessive sound pressure from personal music players that are closely coupled to the ear. It also specifies requirements for earphones and headphones intended for use with personal music players. A personal music player is a portable equipment for personal use, that: is designed to allow the user to listen to recorded or broadcast sound or video; and primarily uses headphones or earphones that can be worn in or on or around the ears; and allows the user to walk around while in use. NOTE 1 Examples are hand-held or body-worn portable CD players, MP3 audio players, mobile phones with MP3 type features, PDA's or similar equipment. A personal music player and earphones or headphones intended to be used with personal music players shall comply with the requirements of this sub-clause. The requirements in this sub-clause are valid for music or video mode only. The requirements do not apply: while the personal music player is connected to an external amplifier; or while the headphones or earphones are not used. NOTE 2 An external amplifier is an amplifier which is not part of the personal music player or the listening device, but which is intended to play the music as a standalone music player. The requirements do not apply to: hearing aid equipment and professional equipment; NOTE 3 Professional equipment is equipment sold through special sales channels. All products sold through normal electronics stores are considered not to be professional equipment.		P
	analogue personal music players (personal music players without any kind of digital processing of the sound signal) that are brought to the market before the end of 2015. NOTE 4 This exemption has been allowed because this technology is falling out of use and it is expected that within a few years it will no longer exist. This exemption will not be extended to other technologies. For equipment which is clearly designed or intended for use by young children, the limits of EN 71-1 apply.		P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.2 Equipment requirements No safety provision is required for equipment that complies with the following: equipment provided as a package (personal music player with its listening device), where the acoustic output $L_{Aeq,T}$ is ≤ 85 dBA measured while playing the fixed “programme simulation noise” as described in EN 50332-1; and a personal music player provided with an analogue electrical output socket for a listening device, where the electrical output is ≤ 27 mV measured as described in EN 50332-2, while playing the fixed “programme simulation noise” as described in EN 50332-1. NOTE 1 Wherever the term acoustic output is used in this clause, the 30 s A-weighted equivalent sound pressure level $L_{Aeq,T}$ is meant. See also Zx.5 and Annex Zx. All other equipment shall: a) protect the user from unintentional acoustic outputs exceeding those mentioned above; and b) have a standard acoustic output level not exceeding those mentioned above, and automatically return to an output level not exceeding those mentioned above when the power is switched off; and	Electrical output: 25mV	P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	c) provide a means to actively inform the user of the increased sound pressure when the equipment is operated with an acoustic output exceeding those mentioned above. Any means used shall be acknowledged by the user before activating a mode of operation which allows for an acoustic output exceeding those mentioned above. The acknowledgement does not need to be repeated more than once every 20 h of cumulative listening time; and NOTE 2 Examples of means include visual or audible signals. Action from the user is always required. NOTE 3 The 20 h listening time is the accumulative listening time, independent how often and how long the personal music player has been switched off. d) have a warning as specified in Zx.3; and e) not exceed the following: 1) equipment provided as a package (player with Its listening device), the acoustic output shall be ≤ 100 dBA measured while playing the fixed “programme simulation noise” described in EN 50332-1; and 2) a personal music player provided with an analogue electrical output socket for a listening device, the electrical output shall be ≤ 150 mV measured as described in EN 50332-2, while playing the fixed “programme simulation noise” described in EN 50332-1. For music where the average sound pressure (long term $L_{Aeq,T}$) measured over the duration of the song is lower than the average produced by the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. In this case T becomes the duration of the song. NOTE 4 Classical music typically has an average sound pressure (long term $L_{Aeq,T}$) which is much lower than the average programme simulation noise. Therefore, if the player is capable to analyse the song and compare it with the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. For example, if the player is set with the programme simulation noise to 85 dBA, but the average music level of the song is only 65 dBA, there is no need to give a warning or ask an acknowledgement as long as the average sound level of the song is not above the basic limit of 85 dBA.	electrical output: 108mV	P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.3 Warning The warning shall be placed on the equipment, or on the packaging, or in the instruction manual and shall consist of the following: the symbol of Figure 1 with a minimum height of 5 mm; and the following wording, or similar: "To prevent possible hearing damage, do not listen at high volume levels for long periods."  **Figure 1 – Warning label (IEC 60417-6044)** Alternatively, the entire warning may be given through the equipment display during use, when the user is asked to acknowledge activation of the higher level.		P
	Zx.4 Requirements for listening devices (headphones and earphones)		
	Zx.4.1 Wired listening devices with analogue input With 94 dBA sound pressure output $L_{Aeq,T}$, the input voltage of the fixed "programme simulation noise" described in EN 50332-2 shall be ≥ 75 mV. This requirement is applicable in any mode where the headphones can operate (active or passive), including any available setting (for example built-in volume level control). NOTE The values of 94 dBA – 75 mV correspond with 85dBA – 27 mV and 100 dBA – 150 mV.		P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	Zx.4.2 Wired listening devices with digital input With any playing device playing the fixed "programme simulation noise" described in EN 50332-1 (and respecting the digital interface standards, where a digital interface standard exists that specifies the equivalent acoustic level), the acoustic output $L_{Aeq,T}$ of the listening device shall be ≤ 100 dBA. This requirement is applicable in any mode where the headphones can operate, including any available setting (for example built-in volume level control, additional sound feature like equalization, etc.). NOTE An example of a wired listening device with digital input is a USB headphone.		P
	Zx.4.3 Wireless listening devices In wireless mode: with any playing and transmitting device playing the fixed programme simulation noise described in EN 50332-1; and respecting the wireless transmission standards, where an air interface standard exists that specifies the equivalent acoustic level; and with volume and sound settings in the listening device (for example built-in volume level control, additional sound feature like equalization, etc.) set to the combination of positions that maximize the measured acoustic output for the abovementioned programme simulation noise, the acoustic output $L_{Aeq,T}$ of the listening device shall be ≤ 100 dBA. NOTE An example of a wireless listening device is a Bluetooth headphone.		P
	Zx.5 Measurement methods Measurements shall be made in accordance with EN 50332-1 or EN 50332-2 as applicable. Unless stated otherwise, the time interval T shall be 30 s. NOTE Test method for wireless equipment provided without listening device should be defined.		P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
2.7.1	Replace the subclause as follows: Basic requirements To protect against excessive current, short-circuits and earth faults in PRIMARY CIRCUITS, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c): a) except as detailed in b) and c), protective devices necessary to comply with the requirements of 5.3 shall be included as parts of the equipment; b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective devices in the building installation;		N/A
	c) it is permitted for PLUGGABLE EQUIPMENT TYPE B or PERMANENTLY CONNECTED EQUIPMENT, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions. If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for PLUGGABLE EQUIPMENT TYPE A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.		N/A
2.7.2	This subclause has been declared 'void'.		N/A
3.2.3	Delete the NOTE in Table 3A, and delete also in this table the conduit sizes in parentheses.		N/A
3.2.5.1	Replace "60245 IEC 53" by "H05 RR-F"; "60227 IEC 52" by "H03 VV-F or H03 VVH2-F"; "60227 IEC 53" by "H05 VV-F or H05 VVH2-F2". In Table 3B, replace the first four lines by the following: Up to and including 6 | 0,75 [a)] | Over 6 up to and including 10| (0,75) [b)] 1,0 | Over 10 up to and including 16| (1,0) [c)] 1,5 | In the conditions applicable to Table 3B delete the words "in some countries" in condition [a)]. In NOTE 1, applicable to Table 3B, delete the second sentence.		N/A
3.2.5.1 (A2:2013)	NOTE Z1 The harmonised code designations corresponding to the IEC cord types are given in Annex ZD		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

IEC 60950-1, GROUP DIFFERENCES (CENELEC common modifications EN)			
Clause	Requirement + Test	Result - Remark	Verdict
3.3.4	In Table 3D, delete the fourth line: conductor sizes for 10 to 13 A, and replace with the following: Over 10 up to and including 16 | 1,5 to 2,5 | 1,5 to 4 | Delete the fifth line: conductor sizes for 13 to 16 A		N/A
4.3.13.6 (A1:2010)	Replace the existing NOTE by the following: NOTE Z1 Attention is drawn to: 1999/519/EC: Council Recommendation on the limitation of exposure of the general public to electromagnetic fields 0 Hz to 300 GHz, and 2006/25/EC: Directive on the minimum health and safety requirements regarding the exposure of workers to risks arising from physical agents (artifical optical radiation).		N/A
	Standards taking into account mentioned Recommendation and Directive which demonstrate compliance with the applicable EU Directive are indicated in the OJEC.		N/A
Annex H	Replace the last paragraph of this annex by: At any point 10 cm from the surface of the OPERATOR ACCESS AREA, the dose rate shall not exceed 1 µSv/h (0,1 mR/h) (see NOTE). Account is taken of the background level. Replace the notes as follows: NOTE These values appear in Directive 96/29/Euratom. Delete NOTE 2.		N/A
Bibliography	Additional EN standards.		—

ZA	**NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS**	—

ZB ANNEX (normative) *SPECIAL NATIONAL CONDITIONS (EN)*			
Clause	Requirement + Test	Result - Remark	Verdict
1.2.4.1	In **Denmark**, certain types of Class I appliances (see 3.2.1.1) may be provided with a plug not establishing earthing conditions when inserted into Danish socket-outlets.		N/A
1.2.13.14 (A11:2009)	In **Norway** and **Sweden**, for requirements see 1.7.2.1 and 7.3 of this annex.		N/A
1.5.7.1 (A11:2009)	In **Finland, Norway** and **Sweden**, resistors bridging BASIC INSULATION in CLASS I PLUGGABLE EQUIPMENT TYPE A must comply with the requirements in 1.5.7.1. In addition when a single resistor is used, the resistor must withstand the resistor test in 1.5.7.2.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative) ***SPECIAL NATIONAL CONDITIONS (EN)***			
Clause	Requirement + Test	Result - Remark	Verdict
1.5.8	In **Norway**, due to the IT power system used (see annex V, Figure V.7), capacitors are required to be rated for the applicable line-to-line voltage (230 V).		N/A
1.5.9.4	In **Finland**, **Norway** and **Sweden**, the third dashed sentence is applicable only to equipment as defined in 6.1.2.2 of this annex.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative)
SPECIAL NATIONAL CONDITIONS (EN)

Clause	Requirement + Test	Result - Remark	Verdict
1.7.2.1	In **Finland**, **Norway** and **Sweden**, CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet. The marking text in the applicable countries shall be as follows: In **Finland**: "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan" In **Norway**: “Apparatet må tilkoples jordet stikkontakt” In **Sweden**: “Apparaten skall anslutas till jordat uttag”		N/A
1.7.2.1 (A11:2009)	In **Norway** and **Sweden**, the screen of the cable distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation need to be isolated from the screen of a cable distribution system. It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by e.g. a retailer. The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in: “Equipment connected to the protective earthing of the building installation through the mains connection or through other equipment with a connection to protective earthing – and to a cable distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a cable distribution system has therefore to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11).”		

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative)
SPECIAL NATIONAL CONDITIONS (EN)

Clause	Requirement + Test	Result - Remark	Verdict
	NOTE In Norway, due to regulation for installations of cable distribution systems, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min. Translation to Norwegian (the Swedish text will also be accepted in Norway): “Utstyr som er koplet til beskyttelsesjord via nettplugg og/eller via annet jordtilkoplet utstyr – og er tilkoplet et kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av utstyret til kabel-TV nettet installeres en galvanisk isolator mellom utstyret og kabel- TV nettet.” Translation to Swedish: ”Utrustning som är kopplad till skyddsjord via jordat vägguttag och/eller via annan utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medföra risk för brand. För att undvika detta skall vid anslutning av utrustningen till kabel-TV nät galvanisk isolator finnas mellan utrustningen och kabel-TV nätet.”		N/A
1.7.2.1 (A2:2013)	In **Denmark**, CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet. The marking text in **Denmark** shall be as follows: In **Denmark**: “Apparatets stikprop skal tilsluttes en stikkontakt med jord, som giver forbindelse til stikproppens jord.”		N/A
1.7.5 1.7.5 (A11:2009)	In **Denmark**, socket-outlets for providing power to other equipment shall be in accordance with the Heavy Current Regulations, Section 107-2-D1, Standard Sheet DK 1-3a, DK 1-5a or DK 1-7a, when used on Class I equipment. For STATIONARY EQUIPMENT the socket-outlet shall be in accordance with Standard Sheet DK 1-1b or DK 1-5a. For **CLASS II EQUIPMENT** the socket outlet shall be in accordance with Standard Sheet DKA 1-4a.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative)
SPECIAL NATIONAL CONDITIONS (EN)

Clause	Requirement + Test	Result - Remark	Verdict
1.7.5 (A2:2013)	In **Denmark**, socket-outlets for providing power to other equipment shall be in accordance with the DS 60884-2-D1:2011. For class I equipment the following Standard Sheets are applicable: DK 1-3a, DK 1-1c, DK 1-1d, DK 1-5a or DK 1-7a, with the exception for STATIONARY EQUIPMENT where the socket-outlets shall be in accordance with Standard Sheet DK 1-1b, DK 1-1c, DK 1-1d or DK 1-5a. Socket outlets intended for providing power to Class II apparatus with a rated current of 2,5 A shall be in accordance with DS 60884-2-D1 standard sheet DKA 1-4a. Other current rating socket outlets shall be in compliance with by DS 60884-2-D1 Standard Sheet DKA 1-3a or DKA 1-3b. Justification the Heavy Current Regulations, 6c		N/A
2.2.4	In **Norway**, for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.3.2	In **Finland**, **Norway** and **Sweden** there are additional requirements for the insulation. See 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.3.4	In **Norway**, for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.6.3.3	In the **United Kingdom**, the current rating of the circuit shall be taken as 13 A, not 16 A.		N/A
2.7.1	In the **United Kingdom**, to protect against excessive currents and short-circuits in the PRIMARY CIRCUIT of DIRECT PLUG-IN EQUIPMENT, tests according to 5.3 shall be conducted, using an external protective device rated 30 A or 32 A. If these tests fail, suitable protective devices shall be included as integral parts of the DIRECT PLUG-IN EQUIPMENT, so that the requirements of 5.3 are met.		N/A
2.10.5.13	In **Finland**, **Norway** and **Sweden**, there are additional requirements for the insulation, see 6.1.2.1 and 6.1.2.2 of this annex.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative)
SPECIAL NATIONAL CONDITIONS (EN)

Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1	In **Switzerland**, supply cords of equipment having a RATED CURRENT not exceeding 10 A shall be provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets: SEV 6532-2.1991 Plug Type 15 3P+N+PE 250/400 V, 10 A SEV 6533-2.1991 Plug Type 11 L+N 250 V, 10 A SEV 6534-2.1991 Plug Type 12 L+N+PE 250 V, 10 A In general, EN 60309 applies for plugs for currents exceeding 10 A. However, a 16 A plug and socket-outlet system is being introduced in Switzerland, the plugs of which are according to the following dimension sheets, published in February 1998: SEV 5932-2.1998: Plug Type 25 , 3L+N+PE 230/400 V, 16 A SEV 5933-2.1998:Plug Type 21, L+N, 250 V, 16A SEV 5934-2.1998: Plug Type 23, L+N+PE 250 V, 16 A		N/A
3.2.1.1	In **Denmark**, supply cords of single-phase equipment having a rated current not exceeding13 A shall be provided with a plug according to the Heavy Current Regulations, Section 107-2-D1. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a. If poly-phase equipment and single-phase equipment having a RATED CURRENT exceeding 13 A is provided with a supply cord with a plug, this plug shall be in accordance with the Heavy Current Regulations, Section 107-2-D1 or EN 60309-2.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)			
Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1 (A2:2013)	In **Denmark**, supply cords of single-phase equipment having a rated current not exceeding 13 A shall be provided with a plug according to DS 60884-2-D1. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a. If a single-phase equipment having a RATED CURRENT exceeding 13 A or if a poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2. Justification the Heavy Current Regulations, 6c		N/A
3.2.1.1	In **Spain**, supply cords of single-phase equipment having a rated current not exceeding 10 A shall be provided with a plug according to UNE 20315:1994. Supply cords of single-phase equipment having a rated current not exceeding 2,5 A shall be provided with a plug according to UNE-EN 50075:1993. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules, shall be provided with a plug in accordance with standard UNE 20315:1994. If poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with UNE-EN 60309-2.		N/A
3.2.1.1	In the **United Kingdom**, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord and plug, shall be fitted with a 'standard plug' in accordance with Statutory Instrument 1768:1994 - The Plugs and Sockets etc. (Safety) Regulations 1994, unless exempted by those regulations. NOTE 'Standard plug' is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative)
SPECIAL NATIONAL CONDITIONS (EN)

Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1	In **Ireland**, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to I.S. 411 by means of that flexible cable or cord and plug, shall be fitted with a 13 A plug in accordance with Statutory Instrument 525:1997 - National Standards Authority of Ireland (section 28) (13 A Plugs and Conversion Adaptors for Domestic Use) Regulations 1997.		N/A
3.2.4	In **Switzerland**, for requirements see 3.2.1.1 of this annex.		N/A
3.2.5.1	In the **United Kingdom**, a power supply cord with conductor of 1,25 mm2 is allowed for equipment with a rated current over 10 A and up to and including 13 A.		N/A
3.3.4	In the **United Kingdom**, the range of conductor sizes of flexible cords to be accepted by terminals for equipment with a RATED CURRENT of over 10 A up to and including 13 A is: • 1,25 mm^2 to 1,5 mm^2 nominal cross-sectional area.		N/A
4.3.6	In the **United Kingdom**, the torque test is performed using a socket outlet complying with BS 1363 part 1:1995, including Amendment 1:1997 and Amendment 2:2003 and the plug part of DIRECT PLUG-IN EQUIPMENT shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16 and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.		N/A
4.3.6	In **Ireland**, DIRECT PLUG-IN EQUIPMENT is known as plug similar devices. Such devices shall comply with Statutory Instrument 526:1997 - National Standards Authority of Ireland (Section 28) (Electrical plugs, plug similar devices and sockets for domestic use) Regulations, 1997.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative)
SPECIAL NATIONAL CONDITIONS (EN)

Clause	Requirement + Test	Result - Remark	Verdict
5.1.7.1	In **Finland**, **Norway** and **Sweden** TOUCH CURRENT measurement results exceeding 3,5 mA r.m.s. are permitted only for the following equipment: • STATIONARY PLUGGABLE EQUIPMENT TYPE A that is intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, for example, in a telecommunication centre; and has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR; and is provided with instructions for the installation of that conductor by a SERVICE PERSON; • STATIONARY PLUGGABLE EQUIPMENT TYPE B; • STATIONARY PERMANENTLY CONNECTED EQUIPMENT.		N/A
6.1.2.1 (A1:2010)	In **Finland**, **Norway** and **Sweden**, add the following text between the first and second paragraph of the compliance clause: If this insulation is solid, including insulation forming part of a component, it shall at least consist of either - two layers of thin sheet material, each of which shall pass the electric strength test below, or - one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below. Alternatively for components, there is no distance through insulation requirements for the insulation consisting of an insulating compound completely filling the casing, so that CLEARANCES and CREEPAGE DISTANCES do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition - passes the tests and inspection criteria of 2.10.11 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 2.10.10 shall be performed using 1,5 kV), and - is subject to ROUTINE TESTING for electric strength during manufacturing, using a test voltage of 1,5 kV.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)			
Clause	Requirement + Test	Result - Remark	Verdict
	It is permitted to bridge this insulation with an optocoupler complying with 2.10.5.4 b). It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005, subclass Y2. A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions: - the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in EN 60950-1:2006, 6.2.2.1; - the additional testing shall be performed on all the test specimens as described in EN 60384-14: - the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.		N/A
6.1.2.2	In **Finland**, **Norway** and **Sweden**, the exclusions are applicable for PERMANENTLY CONNECTED EQUIPMENT, PLUGGABLE EQUIPMENT TYPE B and equipment intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, e.g. in a telecommunication centre, and which has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR and is provided with instructions for the installation of that conductor by a SERVICE PERSON.		N/A
7.2	In **Finland**, **Norway** and **Sweden**, for requirements see 6.1.2.1 and 6.1.2.2 of this annex. The term TELECOMMUNICATION NETWORK in 6.1.2 being replaced by the term CABLE DISTRIBUTION SYSTEM.		N/A
7.3 (A11:2009)	In **Norway** and **Sweden**, for requirements see 1.2.13.14 and 1.7.2.1 of this annex.		N/A

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 1

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Annex ZD
(informative)

IEC and CENELEC code designations for flexible cords

Type of flexible cord	Code designations	
	IEC	CENELEC
PVC insulated cords		
Flat twin tinsel cord	60227 IEC 41	H03VH-Y
Light polyvinyl chloride sheathed flexible cord	60227 IEC 52	H03VV-F H03VVH2-F
Ordinary polyvinyl chloride sheathed flexible cord	60277 IEC 53	H05VV-F H05VVH2-F
Rubber insulated cords		
Braided cord	60245 IEC 51	H03RT-F
Ordinary tough rubber sheathed flexible cord	60245 IEC 53	H05RR-F
Ordinary polychloroprene sheathed flexible cord	60245 IEC 57	H05RN-F
Heavy polychloroprene sheathed flexible cord	60245 IEC 66	H07RN-F
Cords having high flexibility		
Rubber insulated and sheathed cord	60245 IEC 86	H03RR-H
Rubber insulated, crosslinked PVC sheathed cord	60245 IEC 87	H03RV4-H
Crosslinked PVC insulated and sheathed cord	60245 IEC 88	H03V4V4-H

Note: Before placing the products in the different countries, the manufacturer must ensure that:

1. Operating Instructions, Ratings Labels and Warnings Labels written in an Accepted or Official Language of the county in question.
2. The equipment complies with the National Standards and/or Electrical Codes of the country in question.
3. Mains plugs and associated wirings should be assessed to the national standard.

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

EN 62471: 2008

TEST DATA

Table 4.1	Spectral weighting function for assessing ultraviolet hazards for skin and eye.		P
Wavelength[1] λ, nm	**UV hazard function *SUV(λ)***	**Wavelength λ, nm**	**UV hazard function *SUV(λ)***
200	0,030	313*	0,006
205	0,051	315	0,003
210	0,075	316	0,0024
215	0,095	317	0,0020
220	0,120	318	0,0016
225	0,150	319	0,0012
230	0,190	320	0,0010
235	0,240	322	0,00067
240	0,300	323	0,00054
245	0,360	325	0,00050
250	0,430	328	0,00044
254*	0,500	330	0,00041
255	0,520	333*	0,00037
260	0,650	335	0,00034
265	0,810	340	0,00028
270	1,000	345	0,00024
275	0,960	350	0,00020
280	0,960	350	0,00020
285	0,880	355	0,00016
290	0,770	360	0,00013
295	0,540	370	0,00009
297*	0,460	375	0,000077
300	0,300	380	0,000064
303*	0,120	385	0,000053
305	0,060	390	0,000044
308	0,026	395	0,000036
310	0,015	400	0,000030

1 Wavelengths chosen are representative: other values should be obtained bylogarithmic interpolation at intermediate wavelengths.
* Emission lines of a mercury discharge spectrum.

Table 4.2	Spectral weighting functions for assessing retinal hazards from broadband optical sources.	P

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 2

Wavelength nm	Blue-light hazard function *B(λ)*	Burn hazard function *R(λ)*
300	0,01	--
305	0,01	--
310	0,01	--
315	0,01	--
320	0,01	--
325	0,01	--
330	0,01	--
335	0,01	--
340	0,01	--
345	0,01	--
350	0,01	--
355	0,01	--
360	0,01	--
365	0,01	--
370	0,01	--
375	0,01	--
380	0,01	0,1
385	0,013	0,13
390	0,025	0,25
395	0,05	0,5
400	0,10	1,0
405	0,20	2,0
410	0,40	4,0
415	0,80	8,0
420	0,90	9,0
425	0,95	9,5
430	0,98	9,8
435	1,00	10,0
440	1,00	10,0
445	0,97	9,7
450	0,94	9,4
455	0,90	9,0
460	0,80	8,0
465	0,70	7,0
470	0,62	6,2
475	0,55	5,5

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

480	0,45	4,5
485	0,40	4,0
490	0,22	2,2
495	0,16	1,6
500-600	10[(450-λ)/50]	1,0
600-700	0,001	1,0
700-1050	--	10[(700-λ)/500]
1050-1150	--	0,2
1150-1200	--	0,2.100,02(1150-λ)
1200-1400	--	0,02

Table 5.4	**Summary of the ELs for the surface of the skin or cornea (irradiance based values)**				**P**
Hazard Name	**Relevant equation**	**Wavelength range nm**	**Exposure duration sec**	**Limiting aperture rad (deg)**	**EL in terms of constant irradiance $W \cdot m^{-2}$**
Actinic UV skin & eye	$Es = \sum E_\lambda \cdot S(\lambda) \cdot \Delta\lambda$	200 – 400	< 30000	1,4 (80)	30/*t*
Eye UV-A	$E_{UVA} = \sum E_\lambda \cdot \Delta\lambda$	315 – 400	≤1000 >1000	1,4 (80)	10000/*t* 10
Blue-light small source	$E_B = \sum E_\lambda \cdot B(\lambda) \cdot \Delta\lambda$	300 – 700	≤100 >100	< 0,011	100/*t* 1,0
Eye IR	$E_{IR} = \sum E_\lambda \cdot \Delta\lambda$	780 –3000	≤1000 >1000	1,4 (80)	$18000/t^{0,75}$ 100
Skin thermal	$E_H = \sum E_\lambda \cdot \Delta\lambda$	380 – 3000	< 10	2 sr	$20000/t^{0,75}$

Table 5.5	**Summary of the ELs for the retina (radiance based values)**				**P**
Hazard Name	**Relevant equation**	**Wavelength range nm**	**Exposure duration sec**	**Field of view radians**	**EL in terms of constant irradiance $W \cdot m^{-2} \cdot sr^{-1}$**
Blue light	$L_B = \sum L_\lambda \cdot B(\lambda) \cdot \Delta\lambda$	300 – 700	0,25 – 10 10-100 100-10000 ≥10000	$0,011 \cdot \sqrt{(t/10)}$ 0,011 $0,0011 \cdot \sqrt{t}$ 0,1	106/*t* 106/*t* 106/*t* 100
Retinal thermal	$L_R = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$	380 – 1400	< 0,25 0,25 – 10	0,0017 $0,011 \cdot \sqrt{(t/10)}$	$50000/(\alpha \cdot t^{0,25})$ $50000/(\alpha \cdot t^{0,25})$
Retinal thermal (weak visual stimulus)	$L_{IR} = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$	780 – 1400	> 10	0,011	6000/α

Table 6.1	**Emission limits for risk groups of continuous wave lamps(based on EU directive 2006/25/EC)**								**P**
Risk	Action spectrum	Symbol	Units	Emission Measurement					
				Exempt		Low risk		Mod risk	
				Limit	Result	Limit	Result	Limit	Result
Actinic UV	SUV(λ)	Es	$W \cdot m^{-2}$	0,001	4.42×10^{-4}	-	-	-	-

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 2

Table 6.1	**Emission limits for risk groups of continuous wave lamps(based on EU directive 2006/25/EC)**								**P**
Near UV		E_{UVA}	$W•m^{-2}$	0.33	$2.46×10^{-4}$	-	-	-	-
Blue light	B(λ)	L_B	$W•m^{-2}•sr^{-1}$	100	$0.52×10^{2}$	10000	-	4000000	-
Blue light, small source	B(λ)	E_B	$W•m^{-2}$	0.01*	-	1,0	-	400	-
Retinal thermal	R(λ)	L_R	$W•m^{-2}•sr^{-1}$	28000/α	$1.11×10^{3}$	28000/α	-	71000/α	-
Retinal thermal, weak visual stimulus**	R(λ)	L_{IR}	$W•m^{-2}•sr^{-1}$	545000 0.0017≦α≦0.011	-	-	-	-	-
				6000/α 0.011≦α≦0.1	-	-	-	-	-
IR radiation, eye		E_{IR}	$W•m^{-2}$	100	0.99	570	-	3200	-

* Small source defined as one with α < 0,011 radian. Averaging field of view at 10000 s is 0,1 radian.
** Involves evaluation of non-GLS source

Note: The action functions: see Table 4.1 and Table 4.2
The applicable aperture diameters: see 4.2.1
The limitations for the angular subtenses: see 4.2.2
The related measurement condition 5.2.3 and the range of acceptance angles: see Table 5.5

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Maximum sound pressure test
Test specification Standard EN 50332-1:2013
TEST DESCRIPTION

Maximum sound pressure Measurement
Measurement Method

The device under test (DUT) plays the recorded test signal. Earphones or headphones shall be correctly positioned on the HATS. The sound pressure level emitted by the earphones or headphones of the portable audio equipment is measured, for both right and left ear, by a third octave analyzer connected to the microphone of the HATS ear simulator.
The A-weighting curve is applied

Tests are repeated five times for each ear, and the headphone shall be removed and repositioned before each measurement

The A-weighted equivalent continuous sound pressure level L_{Aeq} shall be determined for each measurement, using an averaging time of 30s or more

The maximum sound pressure level considered as the test result is the mean value of all L_{Aeq} measurements.

Table 1：Testing result

No. of measurement	Measured LAeq (dB (A-weighted))		Test duration
	Left channel	Right channel	
1	68.4	68.5	30s
2	68.5	68.4	30s
3	68.4	68.6	30s
4	68.6	68.5	30s
5	68.5	68.4	30s
Mean value of all LAeq	68.5	68.5	--
Remark: Playing mode: the EQ mode is under “ON” condition.			

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 3

Maximum sound pressure test

Test specification Standard EN 50332-2:2013

TEST DESCRIPTION

Maximum sound pressure Measurement

Measurement Method

The method of measurement was described in the order related to the limitation of the maximum output voltage level at the phone jack delivered by the EUT, in accordance with sub-clause 5.2 of EN 50332-2:2013.

a. The test signal used was a programme simulation noise in accordance with clause 5 of EN 50332-1:2013.
b. The player phone output was loaded with a resistive load of 32Ω during the measurement.
c. During the measurement, all controls were adjusted to produce the maximum output voltage level at the phone output.
d. The sum of then maximum wide band output voltage was measured.

Measurement Results

Measurement results showed the maximum RMS voltage for each third-octave frequency bandwidth and the sum of RMS voltage of the output.

Table 1：Testing result

Dynamic bass enhancement(DBB) ON/OFF	Preset sound setting (Rock/POP/Classic/Soft/Jazz)	Left Channel mVmax	Right Channel mVmax	Limit
--	--	78.6	78.2	≤150mV

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 4

Details of: External view-1



Details of: External view-2




Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 4

Details of: External view-3




Details of: External view-4




Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 4

Details of: External view-5




Details of: External view-6




Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 4

Details of: Internal view-1




Details of: PCB view-1




Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 4

Details of: PCB view-2




Details of: PCB view-3



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 4

Details of: PCB view-4




Details of: PCB view-5



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com

Attachment No. 4

Details of: PCB view-6



END OF TEST REPORT

Shenzhen LCS Compliance Testing Laboratory Ltd.
Add：1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel：+(86) 0755-8259 1330 | Fax：+(86) 0755-8259 1332 | E-mail：webmaster@lcs-cert.com | http:// www.lcs-cert.com